								recn	micai	SII	eet no 34	2GM/KAR			
1. Supplier name: GÓRALMET Sp. z o.o.											Supplier address: ul. Krakowska 68, 32-860 Czchów, tel/fax 014 6635260				
2. Pr	oduct nam	e: <b>Repa</b>	ir link											h	÷
te 4. R	chnical para	meters gi annot be i	ven in poi used in the	nt 5. e applica	ations th	at has s						al applications. For use within andards, for example for lifting.			
i. Tec	hnical param	nical parameters: Nominal dimensions [mm]										DE Desekier			
	Size d [mm]											WLL Working load [kG]			
LP.		h [mm]	b [mm]								Weight [kg/pc]	WLL Working load [kG]	BF Breaking force [min. kG]	Material	Coatings
LP.			-			 7	 8	 9	 10	 11		WLL Working load [kG]	force	Material	Coatings
	d [mm]	[mm]	[mm]			7	 8	 9	 10 		[kg/pc]		force [min. kG]		
1	<b>d [mm]</b> 2	[mm] 3	[mm] 4 7,5 9,5	<b></b> 5	 6	 7 	•	-	-	11	[kg/pc]	13	force [min. kG]		
1 1	d [mm] 2 <b>4</b>	[mm] 3 24 26 34	[mm] 4 7,5 9,5 12	 5 	 6 					11	[kg/pc] 12 0,008	13 30	force [min. kG] 14 120	15	16
1 1 2	d [mm] 2 4 5	[mm] 3 24 26 34 36	[mm] 4 7,5 9,5 12 14	5 	6 					11 	[kg/pc] 12 0,008 0,015	13 30 50	force [min. kG] 14 120 200		16
1 2 3 4 5	d [mm] 2 4 5 6 7 8	[mm] 3 24 26 34 36 38	[mm] 4 7,5 9,5 12 14 15	 5  	6  					11  	[kg/pc] 12 0,008 0,015 0,027 0,046 0,064	13 30 50 60 100 140	force [min. kG] 14 120 200 240 400 560	15	16
1 1 2 3 4	d [mm] 2 4 5 6 7	[mm] 3 24 26 34 36	[mm] 4 7,5 9,5 12 14	 5  	6   			  		11   	[kg/pc] 12 0,008 0,015 0,027 0,046	13 30 50 60 100	force [min. kG] 14 120 200 240 400	15	-