
## **Technical sheet No 146GM/KAR**

1. Supplier name: GÓRALMET Sp. z o.o. Supplier address: ul. Krakowska 68, 32-860 Czchów, tel/fax 014 6635260

## 2. Product name: Quick link INOX316

- 3. Description and use: Acid-proof stainless steel links with nut for use as chain accessory, and the other general applications. For use within technical parameters given in point 5.
- 4. Quick links INOX316 cannot be used in the applications that has safety requirements regulated by law or standards, for example for lifting. Do not overload over WLL (kG) given in column 13.



## 5. Technical parameters:

No	Size [mm]	Nominal dimensions [mm]									Mainlet		BF Breaking		
		A [mm]	B [mm]	C min [mm]	D [mm]	L [mm]					Weight [kg/pc]	WLL Working load [kG]	force [min. Kg]	Material	Coatings
1	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16
1	4	20	14	5,5	4	43,5					0,013	90	360	- AISI316	
2	5	23,5	16,5	6	5	49					0,017	145	580		
3	6	27,5	19,5	7	6	58					0,031	185	740		
4	8	34,5	24	9,5	8	74,5					0,074	370	1480		

## 6. Additional informations:

- Safety factor 4
- ▶ BF =4,0 x WLL
- Markings: manufacturer's symbol GMG; SS316; size code (sizes less than 5 size code only)
- Additional informations label: product name; size; quantity; order No; manufacturer's data and website address.