	upplier r	name: GÓR	ALMET Sp	. z o.o.		Suppli	er address: u	I. Krakowsk	ka 68, 32-860 Czc	hów, tel/fax 0	14 6635260)
2. Pr	oduct n	ame: U-bo	It wire rope	e clip						\frown	\cap	
3 D	escriptio	n and use: U	-bolt wire rope	clips is a as	sembly consis	ting of steel U-b	olt bridge and t	he nuts that		\sim	► -1	
a si p	llow for uspendin arameter	two parts of g static load s given in poi	rope to be p s and hangin nt 5. Diameter	oressed togeth ig, with the u of selected with	er when the se of round re rope should	nuts are tighte steel wire rope l be same as nor afety requiremer	ned. Suitable us. For use with ninal size of the	ises include in technical clip.		$\bigcirc \land$	N	1
s	tandards lings for	, for example	as the primary		ces on mine h	oists, crane hois						
	Size								No of grips	Distance betw. grips	For wire ropes up to	
No		Nominal dimensions [mm]					Weight	[N/mm ²]				
		A [mm]	B [mm]	C [mm]				[kg/pc]	[min pcs / loop]	min-max. [mm]	Fiber core	Steel core
1	2	3	4	5	6	7	8	9	10	11	12	13
1	3	M4	16	9				0,008	3	15-30	1770	1570
2	5	M5	19	11				0,014	3	16,5-33	1770	1570
3	6	M5	24	13				0,016	3	18-36	1770	1570
4	8	M6	29	16				0,028	5	21-42	1770	1570
5	10	M8	36	19				0,060	5	27-54	1770	1570
6	11	M8	38	20				0,066	5	28,5-57	1770	1570
	12/13	M10	47	24				0,112	5	34,5-69	1770	1570
	14	M10	50	25				0,123	5	34,5-69	1770	1570
8	16	M12	54	29				0,184	5	39-78	1770	1570
3 Э	19/20	M12	64	32				0,232	6	43,5-87	1770	1570
3 9 0	22	M14	74	37				0,346	7	49,5-99	1770	1570
8 9 0 1		M14	82	41				0,385	7	52,5-105	1770	1570
7 8 9 0 1 2	26	1440	98	48				0,636	8	55,5-111	1770	1570
3 9 0 1 2 3	26 30	M16		52				0,741	8	63-126	1770	1570
3 9 0 1 2 3 4	26 30 34	M16	105									4570
3 0 1 2 3 4	26 30	-	105 127	58				0,934	8	67,5-135	1770	1570
3 9 0 1 2 3	26 30 34	M16				 erial: U-bolt, nuts -		eable cast iron	8	67,5-135	1770	1570